

ACRYLIC PUTTY

for cracks and holes



12.2022 V.02

High quality, ready-to-use, water-based putty, suitable for indoor and outdoor use. It is ideal for plastering all surfaces (plaster, wood, concrete). It spreads easily, without seeping, and when it is rubbed it gives a smooth, ready-to-paint surface. Spread with a spatula in two or more coatings, depending on the surface. It is easily rubbed when it is dry.



Stir well before use



Coverage:
2-3 m²/lt



Drying time:
Touch dry 2 to 3 hrs



Thinning:
Ready to use product



Application:
Spatula

Product Characteristics

- Ready to use
- Easy application
- Easy rubbing

Shades

Available in white. It cannot be tinted.

Packaging:
0,25lt
0.5lt
3lt



The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.

Technical Specifications



V.O.C	5gr/lit (Maximum Volatile Organic Compounds content ready for use).
Density	1,6-1,7 gr/cm ³ (ISO 2811).
Viscosity	Paste texture
pH	7,7-8,7
Performance	Theoretical performance: 2-3m ² /lit, depending on the method of application and the type of surface.
Thinning	Ready to use product- no thinning is required
Application	The product is applied with spatula.
Drying	Touch dry in 2-3 hours. In depth at least 4-6 hours.
Sanding	The product is rubbed after it has dried very well. After at least 4 to 6 hours, depending on the weather conditions.

ACCORDING TO 2004/42/EK

PHASEII,
Subcategory g,
Primers, Limit VOC
value= 30gr/lit,
Maximum VOC
value= 5gr/lit
(product ready for
use).



Storage

Storage indoors to avoid exposure to high or low surfaces and high humidity conditions. Avoid sources of heat, radiation, static electricity, and storage near food. Keep container tightly closed. After opening can use product in a short period of time. Close the can well.



Safety Instructions- Prevention of environmental harming

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. Clean tools with water and soap. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste. Ask for advice from an authorized body for waste recovery. Wear protective gloves and goggles/ Do not eat, drink when handling the product. Wash wand with suitable cleaning products. Keep out of reach of children. Always read the can label before use.
For further information ask for the Safety Data Sheet of the product.

Recommended application systems



Interior/ Exterior walls

- New surfaces / Old- Already painted surfaces

Preparation

Surfaces to be painted should be dry and clean of any dust, grease, salt, and old peeled paints. The product is applied using a spatula. The number of coatings required depends on the surface abnormality. After each coating the product is rubbed with sandpaper. Before sanding, ensure that the coating has dried out well. Repeat with a suitable primer after at least 24 hours.

ACRYLIC PUTTY

2 coats at least

Primer

Prime with Berling's primer suitable for internal use, following its application instructions.

INTERNAL USE PRIMER

1 coat

Final coating

For a uniform and impressive result apply Berling's Emulsion or Acrylic paint of your choice.

EMULSION or ACRYLIC PAINT

2 coats

The above information is based on laboratory audits and the long experience of the scientific staff of the company. The quality of the product is guaranteed by the company's operating system which is based on the requirements of ISO 9001, ISO 45001, ISO 14001 and the EMAS regulation. As producers we are not responsible for any damage or damage caused in the event that the product has not been used for the appropriate application and in accordance with its instructions for use.