

## INVERTER GASOLINE GENERATOR 900 w.

Four Stroke gasoline generator, OHV engine air cooled. Silent Case frame for a better transport and noise reduction. Sine Wave Curve for Electronic Equipment that provides a stable voltage. Adjustable engine speed for lower consumption and noise level allowing up to 4,5 hours autonomy. Oil alert system with automatic engine shut-off.

| DESCRIPTION                            | GENERATOR MODEL                        | GG10i                          | GENERATOR SET        |
|--|--|--------------------------------|----------------------|
| REFERENCE                              |  |                                |                      |
| GENERATOR SET                          | RATED POWER (w)                        | 900                            |                      |
|  | MAX. POWER (w)                         | 1000                           |                      |
|  | FREQUENCY (Hz)                         | 50/60                          |                      |
|  | VOLTAGE (V)                            | 110 / 120 / 220 / 230 / 240    |                      |
|  | CURRENT (A)                            | 11.4 / 10.9 / 10.4             |                      |
|  | SOCKETS                                | 1 x 16A                        |                      |
|  | DISPLAY                                | YES                            |                      |
|  | BATTERY (Ah)                           | -                              |                      |
|  | FUEL TANK CAPACITY (L)                 |                                |                      |
|  | DC OUTPUT (V) / INTENSITY (A)          | 12V / 8.3A                     |                      |
|  | FUEL CONSUMPTION (l/h 50/100% loading) |                                |                      |
| RUNNING TIME UNDER (h 50/100% loading) | 7 h                                    |                                |                      |
| NOISE LEVEL BEHIND 7 METERS (dBA)      | 54-59                                  |                                |                      |
| ENGINE                                 | ENGINE MODEL                           | <b>IC50</b>                    |                      |
|  | Power Output (Kw/5500rpm)              | 1,3 Kw                         |                      |
|  | ROTATE SPEED (RPM)                     | Variable                       |                      |
|  | SPEED REGULATION                       | Electronical                   |                      |
|  | STARTING METHOD                        | Pulling Recoil start           |                      |
|  | DISPLACEMENT (cc)                      | 50 cc.                         |                      |
| ALTERNATOR                             | OIL CAPACITY (L)                       | 0.25 L                         |                      |
|  | ALTERNATOR                             | Inverter                       |                      |
|  | RATED POWER (kW/kVA)                   | 900                            |                      |
|  | POWER FACTOR (Cosφ)                    | 1                              |                      |
| ALARMS                                 | VOLTAGE REGULATION                     | Digital                        |                      |
|  | LOW OIL PRESSURE                       | NO                             |                      |
|  | BLOCK ON START UP                      | NO                             |                      |
|  | LOW OIL LEVEL                          | YES                            |                      |
|  | OVERLOAD INDICATOR                     | YES                            |                      |
| LOGISTICAL DATA                        | EMERGENCY STOP                         | NO                             |                      |
|  | N.G. (kg.)                             | 13                             |                      |
|  | G.W. (kg.)                             | 15                             |                      |
|  | PRODUCT DIMENSIONS (mm)                | 476x271x425                    | 1 x 16A SOCKETS      |
|  | BOX DIMENSIONS (mm)                    |                                | 1 X 12v CONNECTION   |
|  | CAPACITY (units/container)             | 480 pcs FCL20' / 960 pcs FCL40 | 1 X EARTH CONNECTION |



CONTROL PANNEL & CONNECTIONS

Digital display with hourmeter, Voltmeter & Frecuency meter

## RECOMMENDED SPARE PARTS GG10i

| REF. | SPARE PARTS NAME | QTY |
|------|------------------|-----|
|      |                  |     |
|      |                  |     |

300H MAINTENANCE KIT

## OPTIONAL ACCESSORIES GG10i

| REF. | ACCESSORIES NAME  | Set |
|------|-------------------|-----|
|      | Paralel Conection |     |
|      | LED Display       |     |

\*product might be different from pictures shown

\*specifications might vary as continuous product development