

## **DIESEL SILENT GENERATOR**

Diesel generator Silent type, powered by 4 stroke air cooled direct injection engine with electric start, for Industrial aplications, large fuel tank providing long hour running, AVR for smooth voltage output, large muffler to reduce noise harmful effects, oil alert system with automatic engine shut-off, control panel with LED display and overload protection adjustable to prevent damage of the generator.

DESCRIPTION	GENERATOR MODEL	DG6000SE	GENERATOR SET		
	REFERENCE				
GENERATOR SET	RATED POWER (Kw)	5,0			
	MAX. POWER (Kw)	5,5	TCP(IMEP)  DG6000SE		
	FREQUENCY (Hz)	50			
	VOLTAGE (V)	230 v			
	CURRENT (A)	24			
	SOCKETS	2 x 16A			
	DISPLAY	LED5			
	FUEL TANK CAPACITY (L)	14			
	RUNNING TIME - 50% LOAD (hr.)	16			
	NOISE LEVEL BEHIND - 7m. (dBA)	73			
	DC OUTPUT (V) / INTENSITY (A)	12 / 8.3			
	BATTERY (Ah)	36Ah			
ENGINE	ENGINE MODEL	D400E			
	POWER OUTPUT (HP/3000rpm)	10			
	STARTING METHOD	Electric			
	DISPLACEMENT (cc)	418	1		
	OIL CAPACITY (L)	1.65	CONTROL PANNEL		
ALTERNATOR	ALTERNATOR	A5-1S			
	RATED POWER (kW)	5			
	POWER FACTOR (Cosφ)	1	COSTIA, FAMIL  SOUR BELLOCATION  SOUR BELLOCATIO		
	VOLTAGE REGULATION	AVR / Brush			
LOGISTICAL DATA	N.G. (kg.)	152			
	G.W. (kg.)	162	CO TO K LAVON		
	PRODUCT DIMENSIONS (mm)	920x520x760			
	BOX DIMENSIONS (mm)	950x570x790			
	CAPACITY (units/container)	72/FCL20'			

## **RECOMMENDED SPARE PARTS**

REF.	SPARE PARTS NAME	QTY	
SP.DG.ENEB.08.D400	AIR FILTER CORE	1	
SP.DG.ENEB.05.D300/D400	OIL FILTER ELEMENT	1	
SP.DG.FT.12	FUEL FILTER ELEMENT	1	DESCRIPTION. DESCRIPTION. DESCRIPTION. REFERENCE:
SP.ALT.3/5KW.12-S-D	AVR	1	REFERENCE: 7016005 QUANTITY: 1 (31/410021501)

## **OPTIONAL ACCESORIES**

REF.	ACCESSORIES NAME	Set		
	A.T.S. CONTROL BOX	1		•
	LCD CONTROL PANEL	1		
	REMOTE CONTROL	1		
	ATS CONNECTOR FOR CONTROL PANNEL	1		