

Diesel Generator - 3.000 rpm - Full Power



Full Power Switch



STANDARD **ITC Power**
DOMESTIC WARRANTY

- 4-stroke engine, **WATER COOLED**, diesel with direct injection.
- Low oil level alarm with **automatic engine stop**.
- Compact easy installation with **low maintenance** and **low fuel consumption**.
- **Overload protection** by intensity measurement.
- The **FULL POWER** alternator provides 100% three-phase and single-phase power through a selector.
- **Wheels kit** incorporated for an easy transport.

Diesel Generator 3.000 rpm **DG12000XSE-T**

Frequency	50 Hz
Rated Power	11,4 KVA (380) / 9 KW (220)
Max. Power	12,5 KVA (380) / 10 KW (220)
Tension	400 230 V
Current	18 (380) / 42 (220)
Plugs	1xPCE5p (380) / 1x32A(220)
Display	ComAp Intelinano
Tank Capacity	30 L
Running Time 50% load	10 h
Noise Level 7 Mts; 50% load	72 dBA
DC Output	-
Battery	45 Ah

Engine Type	Diesel
Engine Model	EV80
Power Output	16 HP
Start method	Electric
Displacement	794 ml
Oil Capacity	2,27 L
Alternator	KTD5-10
Rated Power	10 kW / 11,5 kW
Power Factor	1 / 0,8
Voltage Regulation	AVR / Brush
Net Weight	318 kg
Gross Weight	360 kg



KAT POWER INTERNATIONAL SL reserves the right to modify the final appearance of the products shown here or replace any item in this catalog without notice. Some technical data are approximate.

KAT POWER INTERNATIONAL SL

Av. Àlguema 6C · 17771 Santa Llogaia d'Àlguema (Girona)
T 972 67 38 36 · info@itcpower.com · www.itcpower.com